

# U-POL™

## SAFETY DATA SHEET

ACID #8

Page 1

Issued: 11/10/2007

Revision No: 4

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** ACID #8

**Product code:** ACID/1

**Use of substance / preparation:** 1K ETCH PRIMER PAINT PRODUCT CONTAINING XYLENE, MIXTURE OF ISOMERS

**Company name:** U-Pol Products

Denington Industrial Estate

Denington Road

Wellingborough

Northants

NN8 2QP

United Kingdom

Tel: +44-(0)-1933 230300

Fax: +44-(0)-1933 230351

Emergency tel: +44-(0)-1933 230310

Email: technical@u-pol.com

### 2. HAZARDS IDENTIFICATION

**Main hazards:** Flammable. Harmful by inhalation, in contact with skin and if swallowed. Irritating to skin. Risk of serious damage to eyes.

**Other hazards:** May cause fire. May cause sensitisation by skin contact.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** XYLENE 10-30%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

• ISOBUTANOL 1-10%

EINECS: 201-148-0 CAS: 78-83-1

[-] R10; [Xi] R37/38; [Xi] R41; [-] R67

• BUTAN-1-OL 10-30%

EINECS: 200-751-6 CAS: 71-36-3

[-] R10; [Xn] R22; [Xi] R37/38; [Xi] R41; [-] R67

[cont...]

**SAFETY DATA SHEET**

ACID #8

- 1-METHOXY-2-PROPANOL 10-30%  
EINECS: 203-539-1 CAS: 107-98-2  
[-] R10
- THERMOPLASTIC ACRYLIC RESIN 10-30%

**4. FIRST AID MEASURES (SYMPTOMS)**

- Skin contact:** There may be irritation and redness at the site of contact.
- Eye contact:** There may be irritation and pain.
- Ingestion:** There may be soreness and redness of the mouth and throat.
- Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**4. FIRST AID MEASURES (ACTION)**

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
- Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
- Ingestion:** Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

**5. FIRE-FIGHTING MEASURES**

- Extinguishing media:** Carbon dioxide. Dry chemical powder. Alcohol or polymer foam. Do not use water.
- Exposure hazards:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions:** Refer to section 8 of SDS for personal protection details.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

**7. HANDLING AND STORAGE**

- Handling requirements:** Ensure there is sufficient ventilation of the area. Smoking is forbidden.
- Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed.
- Suitable packaging:** Must only be kept in original packaging.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

- Workplace exposure limits**
- WEL (8 hr exposure limit):** 50 ppm
- WEL (15 min exposure limit):** 100 ppm
- Respirable dust**
- WEL (8 hr exposure limit):** 1 mg/m<sup>3</sup>

**SAFETY DATA SHEET**

ACID #8

**Hazardous ingredients:** XYLENEWEL (8 hr exposure limit): 220 mg/m<sup>3</sup> WEL (15 min exposure limit): 441 mg/m<sup>3</sup>

## • ISOBUTANOL

WEL (8 hr exposure limit): 154 mg/m<sup>3</sup> WEL (15 min exposure limit): 231 mg/m<sup>3</sup>

## • BUTAN-1-OL

WEL (8 hr exposure limit): 310 mg/m<sup>3</sup> WEL (15 min exposure limit): 154 mg/m<sup>3</sup>

## • 1-METHOXY-2-PROPANOL

WEL (8 hr exposure limit): 375 mg/m<sup>3</sup> WEL (15 min exposure limit): 560 mg/m<sup>3</sup>**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.**Respiratory protection:** Compressed airline breathing apparatus (EN139).**Hand protection:** Nitrile gloves.**Eye protection:** Face-shield.**Skin protection:** Protective clothing with elasticated cuffs and closed neck.**9. PHYSICAL AND CHEMICAL PROPERTIES****State:** Liquid**Colour:** Pale grey**Odour:** Characteristic odour**Evaporation rate:** Moderate**Solubility in water:** Insoluble**Also soluble in:** Most organic solvents.**Viscosity:** Viscous**Viscosity value:** 1500 cps**Flammability limits %: lower:** 1.0**upper:** 6.6**Flash point°C:** 21**Autoflammability°C:** 490**Relative density:** 1.05**VOC g/l:** 670**10. STABILITY AND REACTIVITY****Stability:** Stable under normal conditions.**Conditions to avoid:** Heat. Sources of ignition.**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** XYLENE

ORL MUS LD50 2119 mg/kg

**SAFETY DATA SHEET**

ACID #8

- ORL RAT LD50 4300 mg/kg  
SCU RAT LD50 1700 mg/kg
- ISOBUTANOL  
IVN MUS LD50 417 mg/kg  
IVN RAT LD50 340 mg/kg  
ORL RAT LD50 2460 mg/kg
  - BUTAN-1-OL  
IVN RAT LD50 310 mg/kg  
ORL MUS LD50 2680 mg/kg  
ORL RAT LD50 790 mg/kg
  - 1-METHOXY-2-PROPANOL  
IVN RAT LD50 4200 mg/kg  
ORL MUS LD50 11700 mg/kg  
ORL RAT LDLO 3739 mg/kg

**Chronic toxicity:** May cause sensitisation by skin contact.

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Heavier than water.

**Persistence and degradability:** Not biodegradable.

**Bioaccumulative potential:** No data available.

**Other adverse effects:** Very toxic to aquatic organisms.

**13. DISPOSAL CONSIDERATIONS**

**Disposal operations:** D10 Incineration on land.

R1 Solvent reclamation/regeneration.

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

**UN no:** 1263  
**Packing group:** III  
**Shipping name:** PAINT  
**Labelling:** 3

**ADR Class:** 3  
**Classification code:** F1  
**Hazard ID no:** 30



**SAFETY DATA SHEET**

ACID #8

**IMDG / IMO**

**UN no:** 1263 **Class:** 3  
**Packing group:** III **EmS:** F-E,S-E  
**Marine pollutant:** .  
**Labelling:** 3

**IATA / ICAO**

**UN no:** 1263 **Class:** 3  
**Packing group:** III  
**Packing instructions:** 309(P&CA); 310(CAO)  
**Labelling:** 3

**15. REGULATORY INFORMATION**

**Hazard symbols:** Harmful.



**Risk phrases:** R10: Flammable.  
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.  
R38: Irritating to skin.  
R41: Risk of serious damage to eyes.

**Safety phrases:** S16: Keep away from sources of ignition - No smoking.  
S23: Do not breathe vapour/spray  
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

**Water hazard class:** 1

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

US VOC CONVERSION FACTOR 250 g/l = 2.1 lb/gal

**16. OTHER INFORMATION**

**Other information:** This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.  
FOR PROFESSIONAL USE ONLY. Read full instructions before use.  
IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used.  
Please refer to the label and consult the material safety data sheet for full handling instructions

## SAFETY DATA SHEET

ACID #8

and personal protection information. These are available via your local stockist or via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).

U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

**Risk phrases used in s.3:** R10: Flammable.  
R20/21: Harmful by inhalation and in contact with skin.  
R38: Irritating to skin.  
R37/38: Irritating to respiratory system and skin.  
R41: Risk of serious damage to eyes.  
R67: Vapours may cause drowsiness and dizziness.  
R22: Harmful if swallowed.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.