

U-POL™

SAFETY DATA SHEET

ACID #8 AEROSOL

Page 1

Issued: 05/12/2007

Revision No: 6

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ACID #8 AEROSOL

Product code: ACID/AL

Use of substance / preparation: 1K ETCH PRIMER PAINT PRODUCT CONTAINING XYLENE, MIXTURE OF ISOMERS

Company name: U-Pol Products

Denington Industrial Estate

Denington Road

Wellingborough

Northants

NN8 2QP

United Kingdom

Tel: +44-(0)-1933 230300

Fax: +44-(0)-1933 230351

Emergency tel: +44-(0)-1933 230310

Email: technical@u-pol.com

2. HAZARDS IDENTIFICATION

Main hazards: Extremely flammable. Harmful by inhalation, in contact with skin and if swallowed. Irritating to respiratory system and skin. Risk of serious damage to eyes.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: DIMETHYL ETHER 30-50%

EINECS: 204-065-8 CAS: 115-10-6

[F+] R12

- XYLENE 10-30%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

- 2-METHOXY-1-METHYLETHYL ACETATE 1-10%

EINECS: 203-603-9 CAS: 108-65-6

[-] R10; [Xi] R36

[cont...]

SAFETY DATA SHEET

ACID #8 AEROSOL

- ISOBUTANOL 1-10%
EINECS: 201-148-0 CAS: 78-83-1
[-] R10; [Xi] R37/38; [Xi] R41; [-] R67
- BUTAN-1-OL 1-10%
EINECS: 200-751-6 CAS: 71-36-3
[-] R10; [Xn] R22; [Xi] R37/38; [Xi] R41; [-] R67
- THERMOPLASTIC ACRYLIC RESIN 10-30%
- INERT FILLER 1-10%

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

SAFETY DATA SHEET

ACID #8 AEROSOL

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Workplace exposure limits**

WEL (8 hr exposure limit): 50 ppm

WEL (15 min exposure limit): 100 ppm

Respirable dust

WEL (8 hr exposure limit): 1 mg/m³

Hazardous ingredients: DIMETHYL ETHER

WEL (8 hr exposure limit): 766 mg/m³ WEL (15 min exposure limit): 958 mg/m³

- XYLENE

WEL (8 hr exposure limit): 220 mg/m³ WEL (15 min exposure limit): 441 mg/m³

- 2-METHOXY-1-METHYLETHYL ACETATE

WEL (8 hr exposure limit): 274 mg/m³ WEL (15 min exposure limit): 822 mg/m³

- ISOBUTANOL

WEL (8 hr exposure limit): 154 mg/m³ WEL (15 min exposure limit): 231 mg/m³

- BUTAN-1-OL

WEL (8 hr exposure limit): 310 mg/m³ WEL (15 min exposure limit): 154 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Nitrile gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing with elasticated cuffs and closed neck.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Pale grey

Odour: Characteristic odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

SAFETY DATA SHEET

ACID #8 AEROSOL

Solubility in water: Insoluble
Also soluble in: Most organic solvents.
Flash point°C: -40
Relative density: 0.75
VOC g/l: 675

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.
Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.
Materials to avoid: Strong oxidising agents. Strong acids.
Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: XYLENE
ORL MUS LD50 2119 mg/kg
ORL RAT LD50 4300 mg/kg
SCU RAT LD50 1700 mg/kg

- 2-METHOXY-1-METHYLETHYL ACETATE
IPR MUS LD50 750 mg/kg
ORL RAT LD50 8532 mg/kg
- ISOBUTANOL
IVN MUS LD50 417 mg/kg
IVN RAT LD50 340 mg/kg
ORL RAT LD50 2460 mg/kg
- BUTAN-1-OL
IVN RAT LD50 310 mg/kg
ORL MUS LD50 2680 mg/kg
ORL RAT LD50 790 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.
Persistence and degradability: Biodegradable.
Bioaccumulative potential: No bioaccumulation potential.
Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Disposal operations: D1 Tipping above or underground (e.g. landfill, etc.).
R1 Solvent reclamation/regeneration.
Disposal of packaging: Dispose of as normal industrial waste.

SAFETY DATA SHEET

ACID #8 AEROSOL

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1950 **ADR Class:** 2
Classification code: 5F
Shipping name: AEROSOLS
Labelling: 2.1

**IMDG / IMO**

UN no: 1950 **Class:** 2
EmS: F-D,S-U **Marine pollutant:** .
Labelling: 2.1

IATA / ICAO

UN no: 1950 **Class:** 2
Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Extremely flammable.
Harmful.



Risk phrases: R12: Extremely flammable.
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R37/38: Irritating to respiratory system and skin.
R41: Risk of serious damage to eyes.

Safety phrases: S2: Keep out of the reach of children.
S16: Keep away from sources of ignition - No smoking.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S38: In case of insufficient ventilation, wear suitable respiratory equipment.

SAFETY DATA SHEET

ACID #8 AEROSOL

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Water hazard class: 1

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

US VOC CONVERSION FACTOR 250 g/l = 2.1 lb/gal

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

FOR PROFESSIONAL USE ONLY. Read full instructions before use.

IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used.

Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM.

U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

Risk phrases used in s.3: R12: Extremely flammable.
R10: Flammable.
R20/21: Harmful by inhalation and in contact with skin.
R38: Irritating to skin.
R36: Irritating to eyes.
R37/38: Irritating to respiratory system and skin.
R41: Risk of serious damage to eyes.
R67: Vapours may cause drowsiness and dizziness.
R22: Harmful if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.