



AD16G

INSTANT VALAY [AD16G]

Revision Date: 25/03/2008

SAFETY DATA SHEET



AD16G INSTANT VALAY [AD16G]

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT CODE: AD16G
 PRODUCT NAME: INSTANT VALAY [AD16G]
 MANUFACTURER: Selden Research Limited
 Staden Lane
 Ashbourne Road
 Buxton
 Derbyshire
 SK17 9RZ

TELEPHONE: 01298 26226
 FAX: 01298 26540
 EMAIL: safety@selden.co.uk

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME	EINECS Nr.:	CLASSIFICATION	CONTENT
CAS No.:			
BUTANE			
106-97-8	203-448-7	F+;R12	5-10 %

The full text for all R-Phrases are displayed in Section 16

3. HAZARDS IDENTIFICATION

R12 Extremely flammable.

PRESSURISED CONTAINER - increase in temperature to greater than 50C will cause internal pressure to rise potentially causing bursting/explosion.

4. FIRST AID MEASURES

INHALATION: Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. For breathing difficulties oxygen may be necessary.

INGESTION: Rinse mouth thoroughly. Drink plenty of water. Get medical attention.

SKIN: Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYES: Spray in the eyes.; Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use:., Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES: Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

UNUSUAL FIRE & EXPLOSIVE HAZARDS: Aerosol cans may explode in a fire.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS: Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. If leakage cannot be stopped, evacuate area.

ENVIRONMENTAL PRECAUTIONS: Any spillage needs to be contained and not allowed to enter water courses

7. HANDLING AND STORAGE

USAGE PRECAUTIONS: Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS: Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.



AD16G

INSTANT VALAY [AD16G]
Revision Date: 25/03/2008

SAFETY DATA SHEET



AD16G INSTANT VALAY [AD16G]

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXP 15 Min
BUTANE		WEL	1450 mg/m3	1810 mg/m3

PROTECTIVE EQUIPMENT:



9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Aerosol, White foam
ODOUR:	Slight odour
PHYSICAL DATA COMMENTS:	Information given relates to total aerosol container contents.
FLASH POINT (°C):	- 74
AUTO IGNITION TEMPERATURE (°C):	+ 405
FLAMMABILITY LIMIT - LOWER(%):	1.8
FLAMMABILITY LIMIT - UPPER(%):	10.0

10. STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperature conditions.
CONDITIONS TO AVOID:	Avoid heat, flames and other sources of ignition.
HAZARDOUS COMPOSITION PRODUCTS:	Fire creates: , Vapours/gases/fumes of: , Carbon monoxide (CO). Carbon dioxide (CO2).

11. TOXICOLOGY INFORMATION

INHALATION:	May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.
SKIN CONTACT:	Prolonged or repeated exposure may cause severe irritation.
EYE CONTACT:	Irritation of eyes and mucous membranes.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:	Not regarded as dangerous for the environment.
--------------	--

13. DISPOSAL CONSIDERATIONS

DISPOSABLE METHODS:	Empty containers must not be burned because of explosion hazard., Dispose of waste and residues in accordance with local authority requirements.
---------------------	--

14. TRANSPORT INFORMATION

UN No ROAD:	1950
UK ROAD TRANSPORT CLASS:	2
ADR CLASS NO.:	2
ADR CLASS:	Class 2: Gases
PROPER SHIPPING NAME I:	AEROSOLS, FLAMMABLE
UN No SEA:	1950
IMDG CLASS:	2.1
UN NO. AIR:	1950
ICAO CLASS:	2.1



AD16G

INSTANT VALAY [AD16G]
Revision Date: 25/03/2008

SAFETY DATA SHEET



AD16G INSTANT VALAY [AD16G]

15. REGULATORY INFORMATION

LABEL FOR SUPPLY:



RISK PHRASES:

R12 Extremely flammable.

SAFETY PHRASES:

S2 Keep out of the reach of children, S16 Keep away from sources of ignition - No smoking. S51 Use only in well-ventilated areas.

STATUTORY INSTRUMENTS:

Control of Substances Hazardous to Health. Chemicals (Hazard Information and Packaging) Regulations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

APPROVED CODE OF PRACTICE:

GUIDANCE NOTES:

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

DETERGENT LABELLING:

< 5%	Anionic surfactants
< 5%	Non-ionic surfactants
< 5%	Amphoteric surfactants

16. OTHER INFORMATION

USER NOTES:

The following risk phrases relate to the raw materials in the product and not the product itself:-

REVISION DATE:

25/03/2008

REV. NO./REPL. SDS GENERATED:

2

R-PHRASES (Full Text):

R12 Extremely flammable. |